Listing of Claims

- 1. (currently amended) A method of making a nonwoven web comprising:
 - a) providing a source of fibers;
 - b) subjecting the fibers to an electrostatic charge;
 - c) deflecting the fibers with a non-contacting deflecting device, wherein said noncontact deflecting device comprises an air jet deflector providing discrete jets of air; and
 - d) collecting the fibers on a moving forming surface to form the nonwoven web.
- 2. (original) The method of Claim 1 wherein the fibers are substantially continuous fibers provided by melt spinning.
- 3. (original) The method of Claim 2 wherein the fibers are subjected to pneumatic drawing forces prior to being subjected to the electrostatic charge.
- 4. (canceled)
- 5. (currently amended) The method of Claim 4Claim 1 wherein the air jet deflector provides perturbed jets of air.
- 6. (currently amended) The method of Claim 4Claim 1 wherein the electrostatic charge is provided using a charged pin array.
- 7. (original) The method of Claim 6 wherein the air jet deflector is a target electrode for the charged pin array.
- 8. (currently amended) The method of Claim 4Claim 1 wherein the air jets are angled with respect to the machine direction at an angle of about 15 degrees to about 60 degrees.
- 9. (currently amended) The method of Claim 4 Claim 1 wherein the air jets are angled downward with respect to the horizontal plane at an angle up to about 60 degrees.

Appl. No. 10/687,006 Reply dated June 20, 2006 Reply to Office Action of January 20, 2006

- 10. (canceled)
- 11. (canceled)
- 12. (canceled)
- 13. (canceled)
- 14. (currently amended) An apparatus for forming a fibrous nonwoven web comprising:
 - a) a source of fibers;
 - b) a device for applying an electrostatic charge to the fibers;
 - c) a non-contacting fiber deflecting device adapted to affect the fibers while the fibers are under the influence of the applied electrostatic charge, wherein said non-contact deflecting device comprises an air jet deflector for providing discrete jets of air; and
 - d) a forming surface for collecting the fibers as a fibrous nonwoven web.
- 15. (original) The apparatus of Claim 14 wherein the source of fibers is a melt spinning device for producing continuous fibers and wherein the device for applying the electrostatic charge is a charged pin array, and the apparatus further including a fiber drawing unit applying pneumatic drawing forces to the continuous fibers.
- 16. (original) The apparatus of Claim 15 wherein the device for applying the electrostatic charge to the fibers is located to apply the electrostatic charge before the fibers enter the fiber drawing unit.
- 17. (original) The apparatus of Claim 15 wherein the device for applying the electrostatic charge to the fibers is located to apply the electrostatic charge to the fibers while the fibers are in the fiber drawing unit.

Appl. No. 10/687,006 Reply dated June 20, 2006

Reply to Office Action of January 20, 2006

18. (original) The apparatus of Claim 15 wherein the device for applying the electrostatic charge to the fibers is located to apply the electrostatic charge to the fibers after the fibers exit the fiber drawing unit and before the fibers are collected on the forming surface.

19. (canceled)

20. (canceled)

- 21. (currently amended) The apparatus of Claim 19Claim 17 wherein the air jet deflector is located on the opposite side of the fibers from the device for applying the electrostatic charge, and wherein the air jet deflector is a target electrode.
- 22. (currently amended) The apparatus of Claim 19Claim 18 wherein the air jet deflector is located on the opposite side of the fibers from the device for applying the electrostatic charge, and wherein the air jet deflector is a target electrode.
- 23. (original) The apparatus of Claim 21 wherein the air jets are oriented at an angle with respect to at least one direction selected from the group consisting of the machine direction and the horizontal plane, the angle determined by the desired orientation of the fibers in the nonwoven web.
- 24. (original) The apparatus of Claim 22 wherein the air jets are oriented at an angle with respect to at least one direction selected from the group consisting of the machine direction and the horizontal plane, the angle determined by the desired orientation of the fibers in the nonwoven web.
- 25. (currently amended) The apparatus of Claim 19 Claim 18 further comprising a second air jet deflector located on the opposite side of the fibers from the first air jet deflector.
- 26. (original) The apparatus of Claim 25 wherein the charged pin array is located upon one non-contacting deflection device.